



**GENERAL INFO** **FOR INTERNAL AND EXTERNAL USE**

Standard Filter Housings, 2.5" Diameter

The Puretec Basic HD-B Series filter housings accept a large variety of 2.5" diameter Puretec Basic cartridges for many applications.

**SPECIFICATIONS**

Model Number:	HD1020-B	HD1020-BK	HD1020-BC	HD2020-B
Description:	10" Filter housing silver bowl, black head with pressure relief button	10" Filter housing silver bowl, black head with pressure relief button includes bracket and housing wrench.	10" Filter housing clear bowl, black head with pressure relief button	20" Filter housing silver bowl, black head with pressure relief button
Flow Rate:	38 Lpm	38 Lpm	38 Lpm	76 Lpm
Min/Max Temperature:	0 - 52 °C	0 - 52 °C	0 - 52 °C	0 - 52 °C
Min/Max Pressure:	0 - 875* kPa	0 - 875* kPa	0 - 350* kPa	0 - 875* kPa
Connection:	3/4"	3/4"	3/4"	3/4"
Warranty:	1 year <sup>^</sup>	1 year <sup>^</sup>	1 year <sup>^</sup>	1 year <sup>^</sup>

*Important Note: Use only genuine Puretec replacement cartridge. <sup>^</sup>1 year warranty is 1 year parts and labour. Protect from freezing. Where pressure exceeds 500 kPa a pressure limiting valve must be fitted. \*Where line pressure exceeds 500 kPa, an approved pressure limiting device must be installed to comply with Australian & New Zealand Plumbing Standards. (Ref. AS/NZS 3500.1:2021, Clause 3.3.4). A 350 kPa approved limiting valve must be fitted for clear housings.*

**FEATURES & BENEFITS**

- Internal and external use to suit different applications.
- 1 year warranty<sup>^</sup>.
- Accepts a large variety of 2.5" diameter cartridges.
- Quick and easy installation.

**SPARE PARTS & ACCESSORIES (SOLD SEPARATELY)**

Single Bracket Kit :	<b>HDBK10-B</b>
Double Bracket Kit:	<b>HDBK12-B</b>
Replacement O-Ring:	<b>HDOR-B</b>
Housing Wrench:	<b>HDW10-B</b>

For more information contact your local stockist or visit us at [puretecgroupp.com](http://puretecgroupp.com)  
Australia **1300 140 140** | New Zealand **0800 130 140**